

## Product data sheet

### Characteristics

# NSYTBS16128

ABS box IP66 IK07 RAL7035

Int.H150W105D80 Ext.H164W121D87 Opaque cover H20



### Main

|                     |   |
|---------------------|---|
| Range               | Thalassa TBS  |
| Device application  | Multi-purpose                                       |
| Category            | Industrial box                                      |
| Height              | 164 mm  |
| Width               | 121 mm  |
| Depth               | 87 mm   |
| Internal height     | 150 mm  |
| Internal width      | 105 mm  |
| Internal depth      | 80 mm   |
| Enclosure mounting  | Wall mounted  |
| Device composition  | 4 x cover screw<br>1 x cover<br>1 x body            |
| Quantity per set    | Set of 2  |
| Body type           | One piece moulded                                   |
| Type of front cover | Low plain cover                                     |
| Cover fixing        | Plastic screws                                      |
| Lock type           | Outside sealed area: flat screwdriver captive screw |
| Removable parts     | Cover, by captive screws                            |

### Complementary

|                                     |                                     |
|-------------------------------------|-------------------------------------|
| Material                            | ABS                                 |
| Colour                              | Grey ( RAL 7035 )                   |
| Standards                           | IEC 62208                           |
| Product certifications              | DEMKO<br>SEMKO<br>TÜV               |
| IP degree of protection             | IP66conforming to NEMA 4.4X         |
| IK degree of protection             | IK07conforming to IEC 62262         |
| Fire resistance                     | 650 °C conforming to IEC 60695-2-11 |
| Ambient air temperature for storage | -15...40 °C                         |
| Operating temperature               | -25...60 °C                         |

### Offer Sustainability

|                                  |   |
|----------------------------------|---|
| Sustainable offer status         | Not Green Premium product   |
| RoHS (date code: YYWW)           | Compliant - since 0940 - <a href="#">Schneider Electric declaration of conformity</a> |
| REACH                            | Reference not containing SVHC above the threshold                                     |
| Product end of life instructions | Need no specific recycling operations   |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.